

Centos에서 zabbix설치하기

OS : Centos6

1. 사전에 필요한 툴 : apache, php, mysql

```
$> yum install httpd mysql-server -y
```

2. 필요패키지 설치

```
$> yum install -y net-snmp net-snmp-devel net-snmp-utils curl-devel libxml2-devel
```

3. 컴파일&설치

```
$> groupadd zabbix
$> useradd -g zabbix zabbix

$> tar -zxvf zabbix-2.4.5.tar.gz
$> cd zabbix-2.4.5
$> ./configure \
--prefix=/usr/local/zabbix \
--with-mysql=/usr/local/mysql/bin/mysql_config \
--with-net-snmp \
--with-libcurl \
--with-libxml2 \
--enable-server \
--enable-agent
$> make;make install
```

* 설치경로는 /usr/local/zabbix, mysql설치 경로는 /usr/local/mysql

4. DB구성

```
$> mysql -u root
mysql> create database zabbix;
mysql> grant all privileges on zabbix.* to zabbix@localhost identified by 'zabbix1';
mysql> flush privileges;
mysql> quit
```

```
$> cd database/mysql/
$> mysql -u zabbix -p zabbix < schema.sql
$> mysql -u zabbix -p zabbix < images.sql
$> mysql -u zabbix -p zabbix < data.sql
```

* MYSQL import는 순서대로 하면 됨

5. Frontent 적용

```
$> vi /usr/local/zabbix/etc/zabbix_server.conf
...
DBName=zabbix
DBUser=zabbix
DBPassword=zabbix1
```

*기존내용에서 DBName, DBUser, DBPassword를 위에서 설정한 내용으로 적용하면 됨

6. Frontend 복사

```
$> cp -ar {소스경로}/frontends/php /usr/local/apache2/htdocs/zabbix
```

7. 웹 브라우저로 접속 (기본로그인 ID는 Admin, 패스워드는 zabbix)

`http://서버IP/zabbix`

🕒Revision #1

★Created 8 June 2022 06:11:39 by artop0420

✎Updated 24 December 2023 00:30:55 by artop0420