

LDAP구성-3. SAMBA구성해서 연동하기

Samba서버와 LDAP연동하기 - LDAP서버에서 작업

1. 패키지 설치

```
$> yum install -y samba samba-devel
```

2. samba설정 적용

```
$> vi /etc/samba/smb.conf 내용 추가
...
security = user
ldap admin dn = cn=Manager,dc=my-domain,dc=com
ldap suffix = dc=my-domain,dc=com
ldap group suffix = ou=groups
ldap user suffix = ou=people
ldap passwd sync = yes
ldap delete dn = Yes
domain logons = yes
```

3. LDAP과 samba연동

```
$> vi /etc/openldap/slapd.conf
...
include /etc/openldap/schema/samba.schema
access to attrs=userPassword,sambaLMPassword,smabaNTPassword,shadowLastChange
by dn.children="ou=Manager,dc=my-domain,dc=com" write
by self write
by anonymous auth
by * none
access to *
by dn.children="ou=Manager,dc=my-domain,dc=com" write
by * read
```

4. ldap admin 패스워드 설정

```
$> smbpasswd -w
```

5. LDAP사용자 samba 패스워드 설정

```
$> smbpasswd -a test
$> New SMB password:
$> Retype new SMB password:
```

6. 서비스 시작 및 활성화

```
$> /etc/init.d/smb start
$> chkconfig smb on
```

7. samba 클라이언트 접속 테스트

```
$> smbclient -U test //192.168.10.10/home
```

- 윈도우 장비에서 네트워크 공유폴더를 통해 접근 여부 확인