

# Centos7 oracle 11g 7

## 1. 7 7

```
$> yum -y groupinstall "Desktop" "X Window System" "GNOME Desktop Environment" "Desktop Platform Development" "Desktop Platform"
$> yum -y install glibc* libaio* compat-libstdc* compat-gcc* gcc* libXp* openmotif* compat-db* xorg-x11-deprecated-libs compat-lib*
$> yum install kde-i18n-Korean -y
$> yum install fonts-korean -y
$> yum install -y binutils-2.* compat-libstdc++-33* elfutils* gcc-4.* gcc-c++-4.* glibc-2.* glibc* ksh* libaio* libgomp* libgcc* libstdc++* unixODBC-2* unixODBC-devel* numactl-devel* sysstat* pdksh*
```

### • Centos6 647 7 7 7

```
$> yum install -y xorg-x11-xauth.x86_64 xorg-x11-apps.x86_64
$> yum install -y libXp libXtst binutils compat-db compat-libstdc++-33 glibc glibc-devel glibc-headers gcc gcc-c++ libstdc++ cpp make libaio ksh elfutils-libelf sysstat libaio libaio-devel setarch libXp.i686 libXtst-1.0.99.2-3.el6.i686 glibc-devel.i686 libgcc-4.4.4-13.el6.i686 compat-libstdc++* compat-libf2c* compat-gcc* compat-libgcc* libXt.i686 libXtst.i686
$> yum install -y glibc-2.12-1.7.el6_0.5.i686
```

## 2. 7 7 7

```
$> echo "fs.suid_dumpable = 1
fs.aio-max-nr = 1048576
fs.file-max = 6815744
kernel.shmall = 2097152
kernel.shmmax = 536870912
kernel.shmmni = 4096
# semaphores: semmsl, semmns, semopm, semmni
kernel.sem = 250 32000 100 128
net.ipv4.ip_local_port_range = 9000 65500
net.core.rmem_default=4194304
net.core.rmem_max=4194304
net.core.wmem_default=262144
```

```
net.core.wmem_max=1048586" >> /etc/sysctl.conf
$> sysctl -p
```

### 3. `ulimit` `groupadd`

```
$> echo "oracle          soft  nproc  2047
oracle          hard  nproc  16384
oracle          soft  nofile 4096
oracle          hard  nofile 65536
oracle          soft  stack 10240" >> /etc/security/limits.conf
$> groupadd oinstall
$> useradd -g oinstall oracle
$> passwd oracle
{{ XXXX XX 2X }}
$> mkdir /usr/local/oracle
$> chown oracle.oinstall /usr/local/oracle
```

### 4. OS `redhat-release`

```
mv /etc/redhat-release /etc/redhat-release_ori
echo "redhat-4" > /etc/redhat-release
```

### 5. `cat` `cat` `cat`

```
$> echo "
# Oracle Settings
TMP=/tmp; export TMP
TMPDIR=\$TMP; export TMPDIR
ORACLE_HOSTNAME=orcl.localdomain; export ORACLE_HOSTNAME
ORACLE_UNQNAME=DB11G; export ORACLE_UNQNAME
ORACLE_BASE=/usr/local/oracle; export ORACLE_BASE
ORACLE_HOME=\$ORACLE_BASE/product/11.2.0/db_1; export ORACLE_HOME
ORACLE_SID=orcl; export ORACLE_SID
PATH=/usr/sbin:\$PATH; export PATH
PATH=\$ORACLE_HOME/bin:\$PATH; export PATH
LD_LIBRARY_PATH=\$ORACLE_HOME/lib:/lib:/usr/lib; export LD_LIBRARY_PATH
CLASSPATH=\$ORACLE_HOME/jlib:\$ORACLE_HOME/rdbms/jlib; export CLASSPATH" >> /etc/profile
```

### 6. `cat` `cat` `cat` `cat`

```
$> echo "
source /etc/profile
```

```
su - oracle -c \"\$ORACLE_HOME/bin/lsnrctl start\"  
su - oracle -c \"\$ORACLE_HOME/bin/dbstart\"  
" >> /etc/rc.d/rc.local
```

---

Revision #1

Created 6 June 2022 17:07:55 by artop0420

Updated 8 June 2022 03:58:58 by artop0420