

# mysql

# UUID



mysql       slave status  UUID    .

```
mysql> show slave status \G;
***** 1. row *****

Slave_IO_State:
  Master_Host: 192.168.0.130
  Master_User: repl
  Master_Port: 3306
  Connect_Retry: 60
  Master_Log_File: mysql-bin.000005
  Read_Master_Log_Pos: 502
  Relay_Log_File: localhost-relay-bin.000001
  Relay_Log_Pos: 4
  Relay_Master_Log_File: mysql-bin.000005
  Slave_IO_Running: No
  Slave_SQL_Running: Yes
  Replicate_Do_DB:
  Replicate_Ignore_DB:
  Replicate_Do_Table:
  Replicate_Ignore_Table:
  Replicate_Wild_Do_Table:
  Replicate_Wild_Ignore_Table:
  Last_Errno: 0
  Last_Error:
  Skip_Counter: 0
  Exec_Master_Log_Pos: 502
  Relay_Log_Space: 120
  Until_Condition: None
  Until_Log_File:
  Until_Log_Pos: 0
```



```
mysql> show variables like '%uuid%';
```

```
+-----+-----+  
| Variable_name | Value                                |  
+-----+-----+  
| server_uuid   | 90af1fbb-fe5e-11e5-883a-0050569b3781 |  
+-----+-----+  
1 row in set (0.00 sec)
```

---

Revision #1

Created 6 June 2022 16:46:16 by artop0420

Updated 8 June 2022 04:00:06 by artop0420