

oracle 10g 아카이브 모드 설정

1. 아카이브 모드 상태 확인

```
SQL> archive log list
Database log mode          No Archive Mode
Automatic archival        Disabled
Archive destination        USE_DB_RECOVERY_FILE_DEST
Oldest online log sequence 1
Current log sequence       2
\\SQL> show parameter spfile
\\NAME                     TYPE      VALUE
-----
spfile                     string    /u01/app/oracle/product/10.2.0
                               /db_1/dbs/spfileTSH1.ora
```

2. 아카이브 모드 설정

```
SQL> ALTER SYSTEM SET log_archive_dest_1='location=/u01/app/oracle/oradata/data reopen=60' scope=spfile;
System altered.
\\SQL> ALTER SYSTEM SET log_archive_format='%t_%s_%r.arc' scope=spfile;
System altered.
```

3. Oracle 종료

```
SQL> shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

4. Oracle 시작

```
SQL> startup mount
. ORACLE instance started.
\\Total System Global Area 608174080 bytes
Fixed Size          1220844 bytes
Variable Size       171970324 bytes
Database Buffers    432013312 bytes
Redo Buffers        2969600 bytes
Database mounted.
```

5. log모드 변경

```
SQL> alter database archivelog;
Database altered.
```

6. 아카이브모드 설정내용 확인

```
SQL> archive log list
Database log mode          Archive Mode
Automatic archival        Enabled
Archive destination        /u01/app/oracle/oradata/data
Oldest online log sequence 1
Next log sequence to archive 2
Current log sequence       2
```

7. DB Open

```
SQL> alter database open;
Database altered.
```

8. DB 셧다운 & Cold Backup 권장

```
SQL> shutdown immediate
Database closed.
Database dismounted.
```

ORACLE instance shut down.

9. log파일 생성확인

```
SQL> ALTER SYSTEM SWITCH LOGFILE;  
\\System altered.
```

🕒Revision #1

★Created 6 June 2022 17:13:02 by artop0420

✎Updated 8 June 2022 04:01:09 by artop0420