


oracle 10g 安装



1. 检查数据库状态

```
SQL> archive log list

\\Database log mode          No Archive Mode
Automatic archival           Disabled
Archive destination          USE_DB_RECOVERY_FILE_DEST
Oldest online log sequence   1
Current log sequence         2

\\SQL> show parameter spfile

\\NAME                        TYPE      VALUE
-----
spfile                        string    /u01/app/oracle/product/10.2.0
                               /db_1/dbs/spfileTSH1.ora
```

2. 配置数据库参数

```
SQL> ALTER SYSTEM SET log_archive_dest_1='location=/u01/app/oracle/oradata/data reopen=60' scope=spfile;
System altered.

\\SQL> ALTER SYSTEM SET log_archive_format='%t_%s_%r.arc' scope=spfile;
System altered.
```

3. Oracle 关闭

```
SQL> shutdown immediate

Database closed.

Database dismounted.

ORACLE instance shut down.
```

4. Oracle 启动

```
SQL> startup mount

.ORACLE instance started.

\\Total System Global Area 608174080 bytes
Fixed Size                  1220844 bytes
```

```
Variable Size      171970324 bytes
Database Buffers   432013312 bytes
Redo Buffers       2969600 bytes
Database mounted.
```

5. log 切换

```
SQL> alter database archivelog;
Database altered.
```

6. 查看归档日志配置

```
SQL> archive log list
Database log mode      Archive Mode
Automatic archival     Enabled
Archive destination    /u01/app/oracle/oradata/data
Oldest online log sequence  1
Next log sequence to archive  2
Current log sequence     2
```

7. DB Open

```
SQL> alter database open;
Database altered.
```

8. DB 关闭 & Cold Backup

```
SQL> shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

9. log 切换

```
SQL> ALTER SYSTEM SWITCH LOGFILE;
\\System altered.
```

Revision #1

Created 6 June 2022 17:13:02 by artop0420

Updated 8 June 2022 04:01:09 by artop0420