






puppet

- centos  puppet 
- puppet   

centos puppet



- 1. Master machine
 - 1. ip : 192.168.10.10 / master.localdomain / Centos6
- 2. Agent machine
 - 1. ip : 192.168.10.100 / agent.localdomain / Centos6



- 1. Puppet

```
$> rpm -Uvh http://yum.puppetlabs.com/puppetlabs-release-el-6.noarch.rpm
Retrieving http://yum.puppetlabs.com/puppetlabs-release-el-6.noarch.rpm
warning: /var/tmp/rpm-tmp.Ze6mXg: Header V4 RSA/SHA1 Signature, key ID 4bd6ec30: NOKEY
Preparing... ##### [100%]
package puppetlabs-release-6-11.noarch is already installed
```



- 1. Puppet 1. Puppet

```
[root@master ~]# yum install puppet-server -y
=====
=====
Package      Arch    Version      Repository      Size
=====
=====
Installing:
puppet-server  noarch  3.8.2-1.el6  puppetlabs-products  24 k
Installing for dependencies:
augeas-libs   x86_64  1.0.0-10.el6  base              314 k
```

| | | | | |
|------------------|--------|-------------------|---------------------|-------|
| compat-readline5 | x86_64 | 5.2-17.1.el6 | base | 130 k |
| facter | x86_64 | 1:2.4.4-1.el6 | puppetlabs-products | 99 k |
| hiera | noarch | 1.3.4-1.el6 | puppetlabs-products | 23 k |
| libselenium-ruby | x86_64 | 2.0.94-5.8.el6 | base | 100 k |
| puppet | noarch | 3.8.2-1.el6 | puppetlabs-products | 1.6 M |
| ruby | x86_64 | 1.8.7.374-4.el6_6 | base | 538 k |
| ruby-augeas | x86_64 | 0.4.1-3.el6 | puppetlabs-deps | 21 k |
| ruby-irb | x86_64 | 1.8.7.374-4.el6_6 | base | 317 k |
| ruby-libs | x86_64 | 1.8.7.374-4.el6_6 | base | 1.7 M |
| ruby-rdoc | x86_64 | 1.8.7.374-4.el6_6 | base | 381 k |
| ruby-shadow | x86_64 | 1:2.2.0-2.el6 | puppetlabs-deps | 13 k |
| rubygem-json | x86_64 | 1.5.5-3.el6 | puppetlabs-deps | 763 k |
| rubygems | noarch | 1.3.7-5.el6 | base | 207 k |

Transaction Summary

```
=====
=====
```

Install 15 Package(s)

1. config [] [] [] []

```
[root@master ~]# vi /etc/puppet/puppet.conf

[main]

# The Puppet log directory.
# The default value is '$vardir/log'.
logdir = /var/log/puppet

# Where Puppet PID files are kept.
# The default value is '$vardir/run'.
rundir = /var/run/puppet

# Where SSL certificates are kept.
# The default value is '$confdir/ssl'.
ssldir = $vardir/ssl
moduledir = /etc/puppet/modules

[agent]

# The file in which puppetd stores a list of the classes
```

```
# associated with the retrieved configuration. Can be loaded in
# the separate ``puppet`` executable using the ``--loadclasses``
# option.
# The default value is '$confdir/classes.txt'.
classfile = $vardir/classes.txt
```

```
# Where puppetd caches the local configuration. An
# extension indicating the cache format is added automatically.
# The default value is '$confdir/localconfig'.
localconfig = $vardir/localconfig
```

```
[master]
certname = master.localdomain
moduledir [ ] , certname = master.localdomain [ ] master [ ] [ ]
```

2. [] []

```
[root@master ~]# puppet resource package puppet-server ensure=latest
package { 'puppet-server':
  ensure => '3.8.2-1.el6',
}
```

3. [] []

```
[root@master ~]# /etc/init.d/puppetmaster start
Starting puppetmaster: [ OK ]
```

4. [] []

```
[root@master ~]# netstat -antp | grep LISTEN
tcp    0      0 0.0.0.0:8140          0.0.0.0:*            LISTEN  1127/ruby
tcp    0      0 0.0.0.0:22           0.0.0.0:*            LISTEN  878/sshd
tcp    0      0 127.0.0.1:25         0.0.0.0:*            LISTEN  897/sendmail
tcp    0      0 :::22               :::*                  LISTEN  878/sshd
* tcp/8140 [ ] [ ] [ ] [ ] .
```

2. Agent [] 1. [] []

```
[root@agent ~]# yum install puppet -y
```

```

=====
=====
Package      Arch      Version      Repository      Size
=====
=====
Installing:
puppet      noarch    3.8.2-1.el6    puppetlabs-products  1.6 M
Installing for dependencies:
augeas-libs  x86_64    1.0.0-10.el6    base             314 k
compat-readline5  x86_64    5.2-17.1.el6    base             130 k
facter      x86_64    1:2.4.4-1.el6    puppetlabs-products  99 k
hiera       noarch    1.3.4-1.el6    puppetlabs-products  23 k
libselinux-ruby  x86_64    2.0.94-5.8.el6    base             100 k
ruby        x86_64    1.8.7.374-4.el6_6  base             538 k
ruby-augeas  x86_64    0.4.1-3.el6     puppetlabs-deps     21 k
ruby-irb     x86_64    1.8.7.374-4.el6_6  base             317 k
ruby-libs    x86_64    1.8.7.374-4.el6_6  base             1.7 M
ruby-rdoc    x86_64    1.8.7.374-4.el6_6  base             381 k
ruby-shadow  x86_64    1:2.2.0-2.el6     puppetlabs-deps     13 k
rubygem-json  x86_64    1.5.5-3.el6     puppetlabs-deps     763 k
rubygems     noarch    1.3.7-5.el6     base              207 k

Transaction Summary
=====
=====
Install      14 Package(s)

```

1. `vim` `vim`

```

[root@agent ~]# vi /etc/puppet/puppet.conf
[main]

# The Puppet log directory.
# The default value is '$vardir/log'.
logdir = /var/log/puppet

# Where Puppet PID files are kept.
# The default value is '$vardir/run'.
rundir = /var/run/puppet

```

```

# Where SSL certificates are kept.
# The default value is '$confdir/ssl'.
ssldir = $vardir/ssl

[agent]
# The file in which puppetd stores a list of the classes
# associated with the retrieved configuration. Can be loaded in
# the separate ``puppet`` executable using the ``--loadclasses``
# option.
# The default value is '$confdir/classes.txt'.
classfile = $vardir/classes.txt

# Where puppetd caches the local configuration. An
# extension indicating the cache format is added automatically.
# The default value is '$confdir/localconfig'.
localconfig = $vardir/localconfig
certname=agent.localdomain
runinterval = 60
certname = certname certname certname , runinterval runinterval runinterval runinterval (runinterval) runinterval runinterval .

[root@agent ~]# vi /etc/sysconfig/puppet

# The puppetmaster server
PUPPET_SERVER=master.localdomain

# If you wish to specify the port to connect to do so here
#PUPPET_PORT=8140

# Where to log to. Specify syslog to send log messages to the system log.
PUPPET_LOG=/var/log/puppet/puppet.log

# You may specify other parameters to the puppet client here
#PUPPET_EXTRA_OPTS=--waitforcert=500
PUPPET_SERVER PUPPET_SERVER PUPPET_SERVER PUPPET_SERVER PUPPET_SERVER
PUPPET_LOG PUPPET_LOG PUPPET_LOG PUPPET_LOG PUPPET_LOG

```

2. `certname` `certname`

```
[root@agent ~]# /etc/init.d/puppet start
```

Starting puppet agent: [OK]

```
[root@agent ~]# ps -ef | grep puppet
```

| | | | | | | |
|--|------|---|---|---------|----------|--|
| root | 1072 | 1 | 3 | 16:03 ? | 00:00:00 | /usr/bin/ruby /usr/bin/puppet agent -- |
| server=master.localdomain --logdest=/var/log/puppet/puppet.log | | | | | | |

* ████ ██████ □

| | | | |
|--|--|--|--|
| | | | |
|--|--|--|--|

1.

| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|

| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|

1.    

```
[root@master ~]# puppet cert --sign --list
"agent.localdomain" (SHA256)
52:0D:EF:51:BB:50:99:FE:BC:6D:2F:33:CC:A9:43:73:3B:1C:C6:A1:D6:4C:D2:13:DE:AA:75:E9
:7E:D2:2A:E5
*  +  .
```

2.

```
[root@master ~]# puppet cert --sign agent.localdomain
Notice: Signed certificate request for agent.localdomain
Notice: Removing file Puppet::SSL::CertificateRequest agent.localdomain at
'/var/lib/puppet/ssl/ca/requests/agent.localdomain.pem'
```

3.  

```
[root@master ~]# puppet cert --sign --all --list
+ "agent.localdomain" (SHA256)
9C:18:CA:26:73:CA:65:96:85:07:B1:F4:B7:A3:2C:43:FA:EE:63:3C:A7:A3:6C:CD:A2:51:5B:81:
D2:E5:2D:3F
```

4.

```
[root@master ~]# cat /etc/puppet/manifests/site.pp
file {
  '/tmp/hello' :
    owner => root,
    group => root,
    mode => 444,
    content => "Hello Puppet
by Machine\n";
}
```

```
* /tmp/hello [ ] [ ], [ ] root[ ] [ ] [ ] [ ]  
[ ] 444(read)[ ] , [ ] [ ] Hello Pupples[ ] [ ]
```

5. pupplet

| | | | |
|--|--|--|--|
| | | | |
|--|--|--|--|

```
[root@master ~]# puppet apply /etc/puppet/manifests/site.pp
Notice: Compiled catalog for master in environment production in 0.17 seconds
Notice: /Stage[main]/Main/File[/tmp/hello]/content: content changed
'{md5}723c9d4525cebf11f4e6171740b15abd' to
'{md5}7b1d27a85c9ebf03075ee2150fb4d770'
Notice: Finished catalog run in 0.09 seconds

[ ] )
/tmp/hello[ ] [ ] [ ] [ ] [ ] [ ]
```

2. Agent

```
[root@agent ~]# ls -l /tmp/hello
-r--r--r-- 1 root root 25 Sep 14 16:11 /tmp/hello
[root@agent ~]# cat /tmp/hello
Hello Pupples
by Machine
```

- /tmp/hello[][] [][][][][][] [][]

Reference

- https://docs.puppetlabs.com/guides/install_puppet/install_el.html?_ga=1.81661140.2146970350.1440482857//
- <http://ora-sysdba.tistory.com/entry/Infra-%EC%84%9C%EB%B2%84%EA%B4%80%EB%A6%AC%EC%9D%98-%ED%9A%A8%EC%9C%A8%ED%99%94-Puppet-%EC%84%A4%EC%B9%98//>

puppet

puppet agent   

```
$> puppet agent --configprint all
```