

04. Openstack cli ??

keystone ??

```
[root@openstackdev-1 ~]# . ~/keystonerc_admin
[root@openstackdev-1 ~(keystone_admin)]#
```

??? ????

```
~(keystone_admin)]# openstack image create \
--disk-format qcow2 \
--file CentOS-7-x86_64-GenericCloud-2009.qcow2 \
--public\
Centos7-2009
```

[[[CentOS-7-x86_64-GenericCloud-2009.qcow2 [[[qcow2 [[[, [[[
[[[Centos7-2009, [[[]

???? ??

1. [[[]

```
~(keystone_admin)]# openstack server create \
--flavor m1.small \
--image Centos7-2009 \
--network private \
--boot-from-volume 30 \
--key-name ssh \
--wait \
--max 5 \
client
```

[[[flavor[] m1.small [[[, [[[[Centos7-2009, [[[[private[[
[[, [[[[30G[[client-{n}[[5[] []

2. ????? ????? ??? ??

```
~(keystone_admin)]# openstack server list --all-projects
+-----+-----+-----+
+-----+-----+-----+
| ID                      | Name          | Status |
Networks                  | Image         | Flavor  |
+-----+-----+-----+
+-----+-----+-----+
| 3d728b9b-7c87-4369-8036-ab143af9eb31 | client-2      | ACTIVE |
private=192.168.20.177      | N/A (booted from volume) | m1.small |
| 5427d961-2b6b-4804-85df-c275eddf8e2d | client-3      | ACTIVE |
private=192.168.20.109      | N/A (booted from volume) | m1.small |
| ab7ea5fa-133f-4e10-b5fa-874c4f943720 | client-4      | ACTIVE |
private=192.168.20.115      | N/A (booted from volume) | m1.small |
| cc0974ed-187a-4a19-8a6a-484d477b83c1 | client-1      | ACTIVE |
private=192.168.20.122      | N/A (booted from volume) | m1.small |
| a7e51fdd-cecb-436f-9224-8d1e5d02be28 | ubuntu_sample | ACTIVE |
private=192.168.20.125      | N/A (booted from volume) | m1.small |
+-----+-----+-----+
+-----+-----+-----+
```

3. ????? ?? (?? ????? ??? ??? ??? ?)

```
~(keystone_admin)]# openstack server delete client-1 client-2
```

Revision #2

Created 23 July 2022 16:48:21 by artop0420

Updated 24 December 2023 02:49:01 by artop0420